



MiniCut 5-50

Hose cutting machine, benchtop model

A manually operated cutting machine designed for smaller workshops and service vans. MiniCut is a robust construction, highly reliable and easy to operate. There are three different motor alternatives to choose from; 12V, 230V single phase and 230/400/460V 3-phase. It is prepared with a smoke evacuation connection and it's suitable for braided hoses up to 2".



MiniCut 5-50

Technical data:

Hose capacity 1-2 layer, single phase and 3-phase	3/16" - 2"
Hose capacity 1-2 layer, 12V	1/4" - 1 1/4"
Hose capacity 4 layered, single phase and 3-phase	1/4" - 1 1/4"
Hose capacity 4 layered, 12V	1/4" - 3/4"
Max. hose diameter	80 mm
Motor 12V/single phase/3-phase	1, 1/2, 2/3, 0 kW
Voltage 3-phase	230/400V/16A/50Hz
Voltage single phase	230V/16A/50Hz
Voltage 12V	12V
Velocity	2880 rpm
Diameter (blade), ext.	300 mm
Diameter (blade), int.	50 mm
Connection to external smoke evacuation system	63 mm
Colour	Light grey

Dimensions:

Length	450 mm
Width	400 mm
Height	430 mm
Weight	45 kg

Designation:

MiniCut 5-50, 400V 3-phase

MiniCut 5-50, 230V single phase

MiniCut 5-50, 12V

Part number:

9006-01-00

9006-01-05

9006-03-00

Spare part:

Cutting blade, smooth 300x3x50

Cutting blade, toothed 300x3x50

Part number:

9003-00-03

9003-01-02